

PRODUCT DATA SHEET

AIRTRONIC S2 COMMERCIAL D2L 12V



Second-generation fuel-powered air heater with 2 kW heating power for heating driver's cabs in trucks, transporters, minibuses, motor homes and motor and sailing yachts.

ADVANTAGES:

- Interfaces: CAN, LIN (only 12 V), S+
- Service life 5,000 h
- Brushless motor
- Use of the latest EasyStart Pro and EasyStart Web control units
- Diagnostics and parameter assignment via EasyScan
- Starting capability down to $-46\text{ }^{\circ}\text{C}$
- Stepless heating performance control
- Noise emissions optimized
- Use of acoustically improved metering pump
- Integrated altitude sensor: Automatic altitude adjustment up to 3,000 m
- Optimized combustion

AIRTRONIC S2 COMMERCIAL D2L 12V

Order number	252721050000
Voltage (v)	12
Medium	Air
Fuel	Diesel



CONTROL STAGES

Control stages	Start	Small	Large
Electrical power consumption without water pump	100 W	6 W	31 W
Power		850 W	2,200 W
Fuel consumption		0.1 l/h	0.28 l/h

ATTRIBUTES

Dimensions (l/w/h)	mm x mm x mm
Medium	Air
Operation suitable to x altitude	3,000.00
Upper voltage limit	16.00
Lower voltage limit	10.50