

SOLAR PANEL COMPARISON GUIDE



	ThermoLite			Competitor's Panel	Generic Panel
	26W	36W	100W		
Size	13" x 22"	13" x 29"	22" x 45"	40.5" x 26.5"	14" x 30"
Weight	6 lbs	2 lbs	5 lbs	4 lbs	10 lbs
Output	26W peak output	36W peak output	100W peak output	28W peak output	30W peak output
Install time	30 minutes	60 minutes	90 minutes	90 minutes	At least 60 minutes
Panel Construction	Flexible polymer	Flexible polymer	Flexible polymer	Amorphous silicon	Polycrystalline (Glass)
Warranty	5 years - Full warranty	5 years - Full warranty	5 years - Full warranty	5 years - Limited warranty	1 year - Limited warranty
Install Conditions	Any	40°F-100°F	40°F-100°F	Must be in shade, dry, and between 40°F-80°F	Any
3-Stage Charge Controlling	✓	✓	✓		
High-Flex, Low Temp Automotive Wiring	✓	✓	✓		
Plug & Play Connectivity	✓	✓	✓	✓	
Produces Power In low light	✓	✓	✓	✓	
Automotive Rated	✓	✓	✓		
Unit Mountable	✓	✓			



EXPERT SERVICE AND SUPPORT ARE AS CLOSE AS THIS SIGN.

SUPPORTED BY A NETWORK OF FACTORY-AUTHORIZED SERVICE CENTERS NATIONWIDE!

Choose ThermoLite Solar Panels and enjoy the support of the Thermo King Dealer Network.